

TRIO BOCO

BOILER COAGULANT

TRIO-BOCO; It is a liquid sludge coagulant that prevents the formation of deposits and sludge deposits in the metal parts of both medium and low pressure boilers. By using TRIO-BOCO, sludge is dispersed in small particles and is removed from the boiler with the help of blowdown in the boiler and overheating and pipe splits in the boiler pipes are prevented depending on the deposit. TRIO-BOCO is also easily used when fuel leakage from the feed water into the boiler is observed. By coagulating the fuel droplets, the suspension solids are lowered to the bottom of the boiler and blown out of the boiler. If the fuel leakage is excessive and continuous, the cause of the leakage must be investigated, the leakage must be stopped and off-line cleaning must be carried out.

PRODUCT FEATURES AND BENEFITS

- It is easy to use and economical, reducing the cost of maintenance and cleaning.
- It provides clean boiler water by reducing water consumption.
- It ensures that sludge and oil parts are blown out of the boiler in a floating state.
- It reduces maintenance and operating costs.

DOSAGE AMOUNT AND INTENDED USE

The first dosage of TRIO-BOCO is 20-30 gr. for 1 ton of water and should be continuously added to the tank where hotwell or condensate returns are collected with the help of the dosing pump.

NOTE: Please review the MSDS reports before use for safety, occupational health and safety.