

TRIO T-WELL YAK - 8050

Fuel Conditioner

YAK-8050; It has the feature of dissolving the slurry formed by heavy fuels in the system and mixing it into the fuel. It reduces the amount of sludge by keeping the fuel homogeneous throughout the entire fuel system, providing a stable fuel ready for combustion. It helps achieve fuel compatibility and stability when switching from previously used HSFO fuels to VLSFO fuels.

PRODUCT FEATURES AND BENEFITS

- It stabilizes HSFO and VLSFO fuel mixtures, reducing compatibility problems.
- It dissipates sludge formations and prevents new formations.
- It improves the combustion quality by dispersing fuel components.
- It is an effective corrosion inhibitor in fuel. It prevents abrasion on metal surfaces.
- It reduces deposits such as vanadium, sulfur and sodium.
- It keeps all lines in the fuel system clean and protects against corrosion. It extends the service time of parts and equipment.

DOSAGE AMOUNT AND INTENDED USE

It should be given regularly from the fuel pipeline with the help of a dosing pump. If this method is not possible, it should be poured directly into the fuel tank before the fuel is taken into the tanks.

The amount of use of **YAK-8050** is 2-4 lt for 25 tons of fuel.

NOTE: Please review the MSDS reports before use for safety, occupational health and safety..