

TRIO SOOT CLEAN POWDER

SOOT CLEANER POWDER

TRIO-SOOT CLEAN/POWDER is a powder product that prevents the cleaning and reoccurrence of soot and ash deposits formed on the fire side in the boiler and diesel machine exhaust systems. The residues collected after regular use are cleaned by broom or scraping method. 1mm soot formed in heat exchangers reduces heat efficiency by 10% and 3mm soot accumulation by 40%. TRIO-SOOT CLEAN/POWDER prevents heat losses caused by the soot.

PRODUCT FEATURES AND BENEFITS

- It removes the soot and ash deposits by burning them.
- It reduces smoke, soot and carbon deposits in the system.
- It eliminates the risk of fire from the soot.
- It prevents soot-induced corrosion in the economizer, heat exchangers, exhaust lines.
- It provides cleaning while the boiler is running.
- The product is suitable for use in VLSFO and HSFO fuels.

DOSAGE AMOUNT AND INTENDED USE

It is released to the combustion chamber of the boiler as a chemical direct, the application point for diesel engines is the direct exhaust system.

The usage amount for the boiler and diesel machine system is given below.

BOILER SYSTEM

FUEL CONSUMPTION TONNES/DAY	DOSAGE KG/DAY
5	1
10	2
15	3
20	4
25	5

DIESEL MACHINERY

FUEL CONSUMPTION TONNES/DAY	DOSAGE KG/DAY
10	2
20	3
30	4
40	5
50	6

NOTE: Please review the MSDS reports before use for safety, occupational health and safety.